

Extremely lightweight harness for skitouring, mountaineering and glacier tours.

DESCRIPTION

Construction made of HMPE (high-modulus polyethylene) lace webbing which is super lightweight and strong.

Tying in two color distinguished tying loops with a strength of 15 kN.

Two gear loops with a load capacity of 5 kg. Each gear loop is divided into 3 sections which allow easier gear management. Gear loop is made of thin webbing and long enough that doesn't restraint when wearing a backpack.



Fine nylon fabric inside the harness doesn't absorb water and it is very breathable.

Two slots for the additional plastic carabiner Porter to carry ice screws or other gear.

Opening and adjusting the leg loops with the patented 12 mm wide Rock&Lock aluminium buckle. Easy and fast manipulation even with gloves on.

Two elastic loops on each leg loop for comfortable carrying an ice screw.

KEY FEATURES

- can be put on/off safely and quickly with skis/crampons on with feet on the ground
- super packable size

STANDARDS C € 1019

EN 12277

FEATURES







MATERIALS




- 42 % HMPE
- 37 % PAD
- 12 % light aluminium alloy
- 4% PES
- 3% POM
- 2% rubber





TECHNICAL DATA





		S	М	L	XL
В	A [cm/in]	71-83 / 28-32.6	78-90 / 30.7-35.4	85-97 / 33.4-38.2	92-104 / 36.2-40.9
- 11	B [cm/in]	48-55 / 19-21.6	53-60 / 20.8-23.6	58-65 / 22.8-25.6	63-70 / 24.8-27.5



C5079WB0 Version: 09/2020

COMPARISON

SERAC-FLAKE


- 140 g lighter
- slots for the additional carabiner PORTER
- gear loops divided into 3 sections which allow easier gear management
- rear haul loop with a load capacity of 5 kg
- two elastic loops on each leg loop for comfortable carrying an ice screw



FLAKE

MAINTENANCE

Lifetime of this product depends on the frequency and the environment (salt, sand, moisture, chemicals, etc.) in which is used. Without taking wear or mechanical damage into account and in compliance with the conditions specified in the instructions for use this product may be used 15 years from the date of production and 10 years from the date of the first use.





of salt

beware

of UV



beware of chemicals



drying



instructions

OTHER VIEWS











back view

rear haul loop with a load capacity of 5 kg

slot PORTER

elastic loop for an ice screw

gear loop divided into 3 sections

NC	TE	S																																				
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+
+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+	+

