

	Reference	Certification	Rope diameter	Sheave diameter	Ball bearings	Efficiency	Working load	Weight
Progress capture pulleys								
<b>MICRO TRAXION</b>	P53	CE EN 567	8 to 11 mm	25 mm	Yes	91 %	single: 2,5 kN x 2 = 5 kN rope clamp: 2.5 kN	85 g
<b>PRO TRAXION</b>	P51	CE EN 12278 CE EN 567	8 to 13 mm	38 mm	Yes	95 %	single: 3 kN x 2 = 6 kN rope clamp: 2.5 kN	265 g
High-efficiency pulleys								
<b>PARTNER</b>	P52A	CE EN 12278	7 to 11 mm	25 mm	Yes	91 %	2,5 kN x 2 = 5 kN	56 g
<b>RESCUE</b>	P50A P50AN (black)	CE EN 12278 NFPA 1983 General Use	7 to 13 mm	38 mm	Yes	95 %	4 kN x 2 = 8 kN	185 g
Prusik pulleys								
<b>MINI</b>	P59A	CE EN 12278 NFPA 1983 Light Use	7 to 11 mm	25 mm	Yes	91 %	2,5 kN x 2 = 5 kN	80 g
<b>GEMINI</b>	P66A	CE EN 12278, NFPA 1983 Light Use	7 to 11 mm	25 mm	Yes	91 %	2 x 1,5 kN x 2 = 6 kN	135 g
<b>MINDER</b>	P60A	CE EN 12278, NFPA 1983 General Use	7 to 13 mm	51 mm	Yes	97 %	4 kN x 2 = 8 kN	295 g
<b>TWIN</b>	P65A	CE EN 12278, NFPA 1983 General Use	7 to 13 mm	51 mm	Yes	97 %	2 x 3 kN x 2 = 12 kN	450 g
Single pulleys								
<b>MOBILE</b>	P03A	CE EN 12278	7 to 13 mm	21 mm	No	71 %	2,5 kN x 2 = 5 kN	75 g
<b>FIXE</b>	P05W (yellow) P05WN (black)	CE EN 12278	7 to 13 mm	21 mm	No	71 %	2,5 kN x 2 = 5 kN	90 g
Transport pulleys								
<b>TANDEM</b>	P21	CE EN 12278	rope ≤ 13 mm	21 mm	No	71 %	10 kN	195 g
<b>TANDEM SPEED</b>	P21 SPE	CE EN 12278	rope ≤ 13 mm cable ≤ 12 mm	26 mm	Yes	95 %	10 kN	270 g
Specialized pulleys								
<b>KOOTENAY</b>	P67	CE EN 12278	8 to 19 mm	76 mm	Yes	-	5 kN x 2 = 10 kN	1390 g
<b>ROLLCAB</b>	P47	CE EN 1909	cable ≤ 55 mm	55 mm	No	-	5 kN	1470 g